

New Construction Energy Code Compliance Certificate

Per R401.3 Certificate. A building certificate shall be posted on or in the electrical distribution panel.

Date Certificate Post

Place your
logo here

Mailing Address of the Dwelling or Dwelling Unit

City

Name of Residential Contractor

MN License Number

THERMAL ENVELOPE

Insulation Location	Total R-Value of all Types of Insulation	Type: Check All That Apply							
		Non or Not Applicable	Fiberglass, Blown	Fiberglass, Batts	Foam, Closed Cell	Foam Open Cell	Mineral Fiberboard	Rigid, Extruded Polystyrene	Rigid, Isocynurate
Below Entire Slab									
Foundation Wall									
Perimeter of Slab on Grade									
Rim Joist (1st Floor)									
Rim Joist (2nd Floor+)									
Wall									
Ceiling, flat									
Ceiling, vaulted									
Bay Windows or cantilevered areas									
Floors over unconditioned area									
Describe other insulated areas									

RADON CONTROL SYSTEM

Passive (No Fan)
Active (with fan and monometer or other system monitoring device)
Location (or future location) of Fan:
Other Please Describe Here

Building envelope air tightness:	Duct system air tightness:
----------------------------------	----------------------------

Windows & Doors	Heating or Cooling Ducts Outside Conditioned Spaces
Average U-Factor (excludes skylights and one door) U:	Not applicable, all ducts located in conditioned space
Solar Heat Gain Coefficient (SHGC):	R-value

MECHANICAL SYSTEMS

Appliances	Heating System	Domestic Water Heater	Cooling System	Make-up Air <i>Select a Type</i>
Fuel Type				Not required per mech. code
Manufacturer				Passive
Model				Powered
Rating or Size	Input in BTUS:	Capacity in Gallons:	Output in Tons:	Interlocked with exhaust device. Describe:
Efficiency	AFUE or HSPF%		SEER /EER	Other, describe:
Residential Load Calculation	Heating Loss	Heating Gain	Cooling Load	Location of duct or system:
				Cfm's
				" round duct OR
				" metal duct

MECHANICAL VENTILATION SYSTEM

Describe any additional or combined heating or cooling systems if installed: (e.g. two furnaces or air source heat pump with gas back-up furnace):				Combustion Air <i>Select a Type</i>
Select Type				Not required per mech. code
Heat Recover Ventilator (HRV) Capacity in cfm's:	Low:	High:		Passive
Energy Recover Ventilator (ERV) Capacity in cfm's:	Low:	High:		Other, describe:
Balanced Ventilation capacity in cfm's:				Location of duct or system:
Location of fan(s), describe:				Cfm's
Capacity continuous ventilation rate in cfm's:				" round duct OR
Total ventilation (intermittent + continuous) rate in cfm's:				" metal duct