

# EXCAVATION PERMIT REQUIREMENTS

## **Specifications regulating the making of openings and excavations in streets.**

ORDINANCE NO. 84

SECTION 6: Bituminous surfaced streets disturbed by excavation shall be repaired as follows:

1. All edges of the bituminous surface shall be straight cut by sawing, chiseling or other method approved by the Zoning Administrator.
2. The surface of the crushed rock base shall be brought to an elevation of 2 inches below the surface of the bituminous mat.
3. The bituminous patch material shall conform to Specification 2341 of the MINNESOTA STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION, DATED 1964.
4. The bituminous material shall be thoroughly compacted by use of a steel roller. The minimum thickness of the patch after compaction shall be 2  $\frac{1}{8}$  inches. The surface of the completed patch shall be  $\frac{1}{8}$  inch above the surface of the adjacent bituminous surface and shall conform to the roadway crown.

All backfilling of trenches and excavations and all bituminous patching as required by this ordinance shall be completed within 21 days after the excavation or trenching is completed. If the backfilling and/or patching is not completed within such 21 day period, than the City of La Crescent shall have such backfilling and/or patching done. The amount of such repairs shall be certified to the City of La Crescent Clerk who will collect the sum from the person to whom the permit was issued.